



MiniOne Fixed R25 IP65

02/05/2022

B_SLC1204IP



Product description

The SLC MiniOne Fixed in IP65 is a stylish mini-downlight with high lumen output and a narrow beam angle of 45° - designed for decorative lighting. Get the Final touch on your project with SLC MiniOne. Connect up to 6 downlights on one driver. Can be built-in or mounted on top with the MiniOne Tube accessory. Cut out hole: 25 mm / Built-in height: 18 mm. IP65 (Front) / IP21 (Back)

Technical data

Suitable for built-in mounting	Yes
Adjustability	Not adjustable
With light source	Yes
Surface protection	Powder coating
Voltage type	DC
LED nominal current at constant current	700 - 700 mA
Dimming phase cut-off	Yes
Light sharing	Symmetric
Light outlet	Direct
Degree of protection (IP)	IP65
Rated ambient temperature according to IEC	-10 - °C
Colour rendering index CRI	90-100
Lamp efficacy	54 lm/W
Height/depth	18 mm
Built-in width	25 mm

Suitable for ceiling mounting	Yes
Lamp type	LED not exchangeable
Material housing	Aluminium
Material cover	Other
Nominal voltage	3 - 6 V
Type of control gear	LED operating device current-controlled
Light distributor	Other
Beam angle	Wide beam 41-80°
Rated life time L90/B10 at 25 °C	50000 h
Protection class	II
Colour of light	White
Rated luminous flux according to IEC 62722-	168 lm
Width	32 mm
Length	32 mm
Type of wiring	Suitable for through wiring





Number of poles	2
Luminaire efficacy	53 lm/W
Can be installed directly into the insulation	Yes
Dimming method	Trailing edge
Brand	SLC

Connection type	Pinching contact
Beam angle (°)	45
Cut-out hole (Ø: mm)	25
Dimmable	Yes
Produced by	The Light Group

