



Product Datasheet

06 Downlights Fixed LED>The SMD Dark Light Range

10109D/B/W



9W Dark Light LED Downlight .

Supplied with 300mA non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions





__ 50mm

Gallery



Physical Specification

06 Downlights Fixed LED
The SMD Dark Light Range
10109D/B/W
Black
Die Cast
Circular
50mm

Diameter	120mm
Cutout Hole Diameter	110mm
Recessed Ceiling	Yes
Depth Required	70mm
Indoor	Yes
Adjustable	No
Electrical Characteristics	
Coor	Enternal la alcela d
Gear	External-Included
Fitting + Driver	
	220-240V
Input Voltage 50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	9W
IP Rating	IP20
Light Source	LED built in
Dimmable	No No
F Mark	F
1 Wark	V
Fitting	
Input Type	Constant Current
Input Current	300mA
Voltage	28V
Safety Class	
Power(Watts)	8,1W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835

LED Brand	Sanan
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	7,5-12,6W
Power Factor	0,9
Constant Current	Yes
300mA	25-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	-30? ~ +50?
Housing Material	Plastic
Brand	Lifud
Illumination Data	
Colour Tomporatura	3000K
Colour Temperature Lumen Output	720lm
Light Efficiency	80lm/W
CRI	80
Beam Angle	100°
Illumination Diagram	
Dark Light	Yes
Packing Info	
Box Length	15cm
Box Width	7cm


 Box Height
 13cm

 Pcs/Carton
 50

 Barcode
 5291889060703

 HS Code
 9405409900

Energy Label



Certification & Warranty

Warranty 2 Years
Weee Directive Yes

switch to one light!

