



Product Datasheet

02 Recessed Spots Fixed LED>The Dark Light Pro Range Aluminium

10110FD/W/W



10W COB LED recessed spot, IP20, for general lighting applications.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.













Downloads









Dimensions





100mm

Gallery



Physical Specification

Item Group	02 Recessed Spots Fixed LED
Family	The Dark Light Pro Range Aluminium
Order Code	10110FD/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	100mm

Diameter	75mm
Cutout Hole Diameter	68mm
Recessed Ceiling	Yes
Depth Required	130mm
Indoor	Yes
Adjustable	No
ectrical Characteristics	
Coor	External la plude d
Gear	External-Included
Fitting + Driver	
	000.040\/
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	10W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	300mA
Voltage	30V
Safety Class	
Power(Watts)	9W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Epistar

LED Number	1
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	7,5-12,6W
Power Factor	0,9
Constant Current	Yes
300mA	25-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Brand	LIFUD
Ilumination Data	
Colour Temperature	3000K
Lumen Output	800lm
Light Efficiency	80lm/W
CRI	80
Beam Angle	24°
Illumination Diagram	
Dark Light	Yes
Packing Info	
Box Length	11cm
Box Width	9cm


 Box Height
 12cm

 Pcs/Carton
 50

 Barcode
 5291889057369

 HS Code
 9405409900

Energy Label



Certification & Warranty

Warranty 2 Years

Weee Directive Yes

switch to one light!

