

# **Product Datasheet**

www.1-light.eu

06 Downlights Fixed LED>The Frameless IP65 Range

10115CF/W



15W LED frameless downlight, IP65. Suitable for Indoor/Outdoor installation and bathroom.

Complete with 500mA driver.

Complies with standard EN60598-1 and any other specific standards.











Downloads









Dimensions



## Gallery



#### Related items







050146/W

## **Physical Specification**

Item Group

06 Downlights Fixed LED

Family

The Frameless IP65 Range

Order Code	10115CF/W
Colour	White
Material	Die Cast
Diffuser Material	PC
Shape	Circular
Height	22mm
Diameter	155mm
Cutout Hole Diameter	135mm
Recessed Ceiling	Yes
Depth Required	50mm
Indoor	Yes
Outdoor	Yes
Adjustable	No
IK Rating	8
Electrical Characteristics	
Electrical Characteristics  Gear	External-Included
Gear	External-Included
Gear Fitting + Driver	
Gear	External-Included  220-240V
Gear Fitting + Driver	
Gear  Fitting + Driver  Input Voltage	220-240V
Gear  Fitting + Driver  Input Voltage  50 Hz	220-240V Yes
Gear  Fitting + Driver  Input Voltage  50 Hz  60 Hz	220-240V Yes
Gear  Fitting + Driver  Input Voltage  50 Hz  60 Hz  Safety Class	220-240V Yes Yes
Gear  Fitting + Driver  Input Voltage  50 Hz  60 Hz  Safety Class  Power(Watts)	220-240V Yes Yes
Fitting + Driver  Input Voltage  50 Hz  60 Hz  Safety Class  Power(Watts)  IP Rating	220-240V Yes Yes  15W IP65
Gear  Fitting + Driver  Input Voltage  50 Hz  60 Hz  Safety Class  Power(Watts)  IP Rating  Light Source	220-240V Yes Yes  15W IP65 LED built in
Fitting + Driver  Input Voltage  50 Hz  60 Hz  Safety Class  Power(Watts)  IP Rating  Light Source  Dimmable	220-240V Yes Yes In the state of the state o
Fitting + Driver  Input Voltage  50 Hz  60 Hz  Safety Class  Power(Watts)  IP Rating  Light Source  Dimmable	220-240V Yes Yes In the state of the state o

Input Current	500mA
Voltage	22,5V
Safety Class	ŢII]
Power(Watts)	11,25W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 4014
LED Brand	Zhaochi
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	8,5-12W
Power Factor	0,9
Constant Current	Yes
500mA	17-24V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Kegu
Ilumination Data	
Colour Tomporoture	2000K
Colour Temperature	3000K
Lumen Output	1650lm
Light Efficiency	110lm/W
CRI	80

Beam Angle		
Beam Angle		

Illumination Diagram

Warranty

Packing Info		
Box Length	21cm	
Box Width	19,5cm	
Box Height	3cm	
Box Weight	0,46Kg	
Pcs/Carton	20	
Carton Length	43cm	
Carton Width	37cm	
Carton Height	22cm	
Carton Weight	9,4Kg	
Barcode	5291889057109	
HS Code	9405409900	

120°

# Certification & Warranty

Weee Directive Yes

5 Years



