

06 Downlights Fixed LED>The IP54 Bathroom Downlights

10118B/W/W



18W LED recessed downlight, IP54. Suitable for bathroom installations.

Supplied with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery






Physical Specification

Item Group	06 Downlights Fixed LED
Family	The IP54 Bathroom Downlights
Order Code	10118B/W/W
Colour	White
Material	Die Cast
Diffuser Material	Plastic
Shape	Circular

Height	45mm
Diameter	170mm
Cutout Hole Diameter	140mm
Recessed Ceiling	Yes
Depth Required	70mm
Indoor	Yes
Outdoor	Yes
Adjustable	No


Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	18W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	


Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	34V
Safety Class	
Power(Watts)	17W
IP Rating	IP54
Light Source	LED built in

LED Type	SMD 2835
LED Brand	Epistar
F Mark	

Gear

Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	13,5-20W
Power Factor	0,9
Constant Current	Yes
500mA	27-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	45°C
Operating Temp	80°C
Housing Material	Plastic
Output Terminal	Cable
Brand	0
Protection	Short Circuit and Overload


Illumination Data

Colour Temperature	3000K
Lumen Output	1300lm
Light Efficiency	72,22lm/W
CRI	80
Beam Angle	90°
Illumination Diagram	

Packing Info

Box Length	18,5cm
Box Width	18,5cm
Box Height	9cm
Pcs/Carton	30
Barcode	5291889057703
HS Code	9405409900

Energy Label



Certification & Warranty

Warranty	2 Years
Average Lifetime	40000hrs
Weee Directive	Yes

switch to
one light!

one
LIGHT

