



Product Datasheet

04 Recessed Spots Adjustable LED>The IP44 & IP54 COB

11207WD/W/W

Outdoor/Bathroom Range Aluminium



2x7W LED Dark Light Recessed adjustable spot, IP54.

Requires 700mA driver.

Complies with standard EN60598-1 and any other specific standards.



















Downloads










Dimensions









Gallery



Must be ordered separately



89015A

Related items



89015AT

Physical Specification

Item Group	04 Recessed Spots Adjustable LED
Family	The IP44 & IP54 COB Outdoor/Bathroom Range Aluminium
Order Code	11207WD/W/W
Colour	White
Material	Die Cast
Shape	Rectangular
Length	168mm
Width	90mm
Height	83mm
Cutout Hole Width	160mm
Cutout Hole Length	83mm
Recessed Ceiling	Yes
Depth Required	100mm
Indoor	Yes
Outdoor	Yes
Adjustable	1 Direction

Electrical Characteristics

Fitting	
Input Type	Constant Current
Input Current	700mA
Safety Class	
Power(Watts)	7W

IP Rating	IP54
Light Source	LED built in
LED Type	СОВ
LED Brand	Bridgelux
LED Number	1
Cable Length	40cm
F Mark	F

Illumination Data	
Colour Temperature	3000K
Lumen Output	350lm
Light Efficiency	50lm/W
CRI	90
Beam Angle	36°
Illumination Diagram	
Dark Light	Yes

Packing Info	
Box Length	17,5cm
Box Width	9,5cm
Box Height	10cm
Box Weight	0,520Kg
Pcs/Carton	16
Barcode	5291889050704
HS Code	9405409900

Certification & Warranty

Warranty	3 Years
Weee Directive	Yes



