O_{LIGHT}

Product Datasheet

14 Wall & Ceiling LED>Adjustable COB Cylinders

12108XA/W/W



Surface dimmable cylinder with COB LED.


Complete with 350mA constant current dimmable driver.

Complies with standard EN60598-1 and any other specific standards.





Dimensions



Physical Specification

Item Group	14 Wall & Ceiling LED
Family	Adjustable COB Cylinders
Order Code	12108XA/W/W
Colour	White
Material	Aluminium
Shape	Rectangular
Length	80mm

Width	80mm
Height	100mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No



Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	8W
IP Rating	IP20
Light Source	LED built in
Dimmable	Yes
Dimmer type	Triac
F Mark	F
Fitting	

Input Type
Input Current
Voltage
Safety Class
Power(Watts)
IP Rating
Light Source
LED Type
LED Brand

Constant Current
350mA
20V
7W
IP20
LED built in
СОВ
Citizen

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes



Power(Watts)	4,2-8,4W
Power Factor	0,9
Constant Current	Yes
350mA	12-24V
IP Rating	IP20
Safety Class	
Housing Material	Plastic
Brand	AIDimming


Illumination Data

Colour Temperature	3000K
Lumen Output	640lm
Light Efficiency	80lm/W
CRI	90
Beam Angle	36°
Illumination Diagram	

Packing Info

Pcs/Carton	36
Barcode	5291889064718
HS Code	9405409900

Energy Label





Warranty	3 Years
Weee Directive	Yes

switch to one light!

Certification & Warranty



