

14 Wall & Ceiling LED>The SMD Cylinders Aluminium

## 12115L/B/W



15W SMD LED ceiling downlight, ideal for residential and commercial illumination.

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



### Downloads



### Dimensions



### Physical Specification

Item Group	14 Wall & Ceiling LED
Family	The SMD Cylinders Aluminium
Order Code	12115L/B/W
Colour	Black
Material	Aluminium
Shape	Circular
Height	100mm
Diameter	130mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No

## Gear

## Built In

## Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

15W

IP Rating

IP40

Light Source

LED built in

Dimmable

No

F Mark



## Fitting

Input Type

Constant Current

Input Current

300mA

Voltage

45V

Power(Watts)

13,5W

IP Rating

IP20

Light Source

LED built in

LED Type

SMD 5630

LED Brand

Samsung

## Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Power(Watts)


9,5-15W

Power Factor

0,9

Constant Current	Yes
350mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Brand	XY

### Illumination Data

Colour Temperature	3000K
Lumen Output	1280lm
Light Efficiency	85,33lm/W
CRI	80
Beam Angle	90°
Illumination Diagram	

### Packing Info

Box Length	14cm
Box Width	14cm
Box Height	11cm
Box Weight	0,5Kg
Pcs/Carton	36
Barcode	5291889062110
HS Code	9405409900

### Energy Label



## Certification & Warranty

Warranty

2 Years

Weee Directive

Yes

switch to  
**one light!**

**one**  
LIGHT

