



Product Datasheet

12 Office & Kitchen>Recessed LED Linear Profiles

38145BR/W/C



40W UGR19 Recessed linear with 48pcs LED spots, ideal for offices.


Complete with 1000mA driver, 6pcs fixing clips, 4pcs connectors & 2pcs end cups. .

Can be connected in line

Complies with standard EN60598-1 and any other specific standards.



Downloads IES CE



Gallery



Physical Specification Item Group 12 Office & Kitchen Family Recessed LED Linear Profiles Order Code 38145BR/W/C Colour White Material Aluminium Shape Rectangular Length 1295mm

Width	50mm
Height	55mm
Cutout Hole Width	1280mm
Cutout Hole Length	37mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

LED Type

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	1000mA
Voltage	38V
Power(Watts)	38W
IP Rating	IP20
Light Source	LED built in

SMD 3030

LED Brand	Osram
LED Number	48
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	30-42W
Power Factor	0,9
Constant Current	Yes
1000mA	30-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Brand	AGT
Illumination Data	
	100017
Colour Temperature	4000K
Lumen Output	4000lm
Light Efficiency	100lm/W
CRI	80
Beam Angle	34°
Illumination Diagram	
Dark Light	Yes

Packing Info

Pcs/Carton 12


Barcode

HS Code

5291889062714

9405409900

Energy Label



Certification & Warranty

Warranty	3 Years
Weee Directive	Yes

switch to one light!

