



Product Datasheet

08 Downlights Adjustable LED>The Shop Classic Rectangle Die cast

51140/B/W



40W COB LED Recessed adjustable downlight, COB square range, IP20.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.











Downloads









Dimensions




Physical Specification

Item Group	08 Downlights Adjustable LED
Family	The Shop Classic Rectangle Die cast
Order Code	51140/B/W
Colour	Black
Material	Aluminium
Shape	Rectangular
Length	235mm
Width	145mm
Height	110mm
Cutout Hole Width	220mm
Cutout Hole Length	130mm
Recessed Ceiling	Yes

Depth Required	140mm
Indoor	Yes
Adjustable	1 Direction
Electrical Characteristics	
Gear	External-Included
Fitting I Driver	
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	1050mA
Voltage	35V
Safety Class	ŢIII N
Power(Watts)	37W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Sanan
Gear	
Gear Type	Led Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	34,65-42W
Power Factor	0,9
Constant Current	Yes
1050mA	33-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Brand	Lifud
Illumination Data	
Illumination Data	
Illumination Data Colour Temperature	3000K
	3000K 3400lm
Colour Temperature	
Colour Temperature Lumen Output	3400lm
Colour Temperature Lumen Output Light Efficiency	3400lm 85lm/W
Colour Temperature Lumen Output Light Efficiency CRI	3400lm 85lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	3400lm 85lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	3400lm 85lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3400lm 85lm/W 80 70°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Pcs/Carton	3400lm 85lm/W 80 70°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3400lm 85lm/W 80 70°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Pcs/Carton	3400lm 85lm/W 80 70°



Certification & Warranty

Warranty	2 Years
Weee Directive	Yes



