

14 Plafo>The Ultra Slim LED Floating Plafo Aluminium

62160FB/B/C



60W LED slim plafo light, IP20, suitable for residential and commercial application.

Supplied with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

| | |
|-----------------|---|
| Item Group | 14 Plafo |
| Family | The Ultra Slim LED Floating Plafo Aluminium |
| Order Code | 62160FB/B/C |
| Colour | Black |
| Material | Aluminium |
| Shape | Circular |
| Height | 55mm |
| Diameter | 600mm |
| Surface Ceiling | Yes |
| Indoor | Yes |
| Adjustable | No |

Gear

External-Included

Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

60W

IP Rating

IP20

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current

1500mA

Voltage

39V

Safety Class



Power(Watts)

58,5W

IP Rating

IP20

Light Source

LED built in

LED Type

SMD 2835

LED Brand

Sanan

F Mark



Gear

Gear Type

Led Driver

Input Voltage


220-240V

50 Hz


Yes

60 Hz

Yes

| | |
|---------------------|---|
| Power(Watts) | 37,5-63W |
| Power Factor | 0,9 |
| Constant Current | Yes |
| 1500mA | 25-42V |
| IP Rating | IP20 |
| Safety Class |  |
| Dimmable | No |
| Ambient Temp | 40°C |
| Operating Temp | 80°C |
| Housing Material | Plastic |
| Output Terminal | Cable |
| Fast Connector | Yes |
| Fast Connector Type | Other |
| Brand | Lifud |

Illumination Data

| | |
|----------------------|---|
| Colour Temperature | 4000K |
| Lumen Output | 5300lm |
| Light Efficiency | 88,33lm/W |
| CRI | 80 |
| Illumination Diagram |  |

Packing Info

| | |
|------------|---------------|
| Box Weight | 4.140kg |
| Pcs/Carton | 3 |
| Barcode | 5291889057451 |
| HS Code | 9405413990 |

Warranty

3 Years

Weee Directive

Yes

switch to
one light!

one
LIGHT

