

Product Datasheet

www.1-light.eu

10 Track Spots>The COB Track Spot Range Aluminium

65611NT/W/C



15W track spot with COB LED, ideal for shops and showrooms.

Complete with driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Related items







40003A/W


Physical Specification

Item Group	10 Track Spots
Family	The COB Track Spot Range Aluminium
Order Code	65611NT/W/C
Colour	White
Material	Aluminium
Shape	Circular
Height	110mm

Diameter	80mm
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions
lectrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	15W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	400mA
Voltage	36V
Safety Class	ŢIII>
Power(Watts)	14,4W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Sanan
Gear	
Gear Type	Led Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	10-16W
Power Factor	0,9
Constant Current	Yes
400mA	25-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Lifud
Protection	Short Circuit Protection
Ilumination Data	
Ilumination Data Colour Temperature	4000K
	4000K 1300lm
Colour Temperature	
Colour Temperature Lumen Output	1300lm
Colour Temperature Lumen Output Light Efficiency	1300lm 86,67lm/W
Colour Temperature Lumen Output Light Efficiency CRI	1300lm 86,67lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	1300lm 86,67lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	1300lm 86,67lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	1300lm 86,67lm/W 80 38°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	1300lm 86,67lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	1300lm 86,67lm/W 80 38°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	1300lm 86,67lm/W 80 38°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width	1300lm 86,67lm/W 80 38° 25cm 13cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height	1300lm 86,67lm/VV 80 38° 25cm 13cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height Pcs/Carton	1300lm 86,67lm/W 80 38° 25cm 13cm 10cm

Energy Label



Certification & Warranty

Warranty	2 Years
Weee Directive	Yes

one

switch to one light!

