

Product Datasheet

www.1-light.eu

10 Track Spots>The COB Track Spot Range Aluminium

65612NT/B/C



30W track spot with COB LED, ideal for shops and showrooms.

Complete with driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Related items







40003A/B

Physical Specification

| Item Group | 10 Track Spots |
|------------|------------------------------------|
| Family | The COB Track Spot Range Aluminium |
| Order Code | 65612NT/B/C |
| Colour | Black |
| Material | Aluminium |
| Shape | Circular |
| Height | 123mm |
| | |

| Diameter | 90mm |
|--------------------------|------------------|
| Track mounted | Yes |
| Indoor | Yes |
| Adjustable | 2 Directions |
| | |
| ectrical Characteristics | |
| | |
| Gear | Built In |
| Fitting + Driver | |
| | |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class | |
| Power(Watts) | 30W |
| IP Rating | IP20 |
| Light Source | LED built in |
| Dimmable | No |
| | |
| Fitting | |
| Input Type | Constant Current |
| Input Current | 750mA |
| Voltage | 38V |
| Safety Class | <u> </u> |
| Power(Watts) | 28,5W |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | СОВ |
| LED Brand | Sanan |
| | |
| Gear | |
| | |

| 50 Hz | |
|---|--|
| | |
| 60 Hz | |
| Power(Watts) 25-30W | |
| Power Factor 0,9 | |
| Constant Current Yes | |
| 750mA 33-40V | |
| IP Rating IP20 | |
| Safety Class | |
| Dimmable | |
| Housing Material Plastic | |
| Output Terminal Connector | |
| Brand Lifud | |
| Direct action | |
| Protection Short Circuit Protection | |
| Short Circuit Protection | |
| Ilumination Data | |
| Ilumination Data | |
| | |
| Ilumination Data | |
| Illumination Data Colour Temperature 4000K | |
| Illumination Data Colour Temperature 4000K Lumen Output 2500lm | |
| Colour Temperature | |
| Colour Temperature 4000K Lumen Output 2500Im Light Efficiency 83,33Im/W CRI 80 | |
| Colour Temperature 4000K Lumen Output 2500Im Light Efficiency 83,33Im/W CRI 80 Beam Angle 38° | |
| Colour Temperature 4000K Lumen Output 2500lm Light Efficiency 83,33lm/W CRI 80 Beam Angle 38° Illumination Diagram | |
| Colour Temperature | |
| Colour Temperature 4000K Lumen Output 2500Im Light Efficiency 83,33Im/W CRI 80 Beam Angle 38° Illumination Diagram Packing Info Box Length 25cm | |
| Colour Temperature | |
| Colour Temperature 4000K Lumen Output 2500Im Light Efficiency 83,33Im/W CRI 80 Beam Angle 38° Illumination Diagram Packing Info Box Length 25cm | |
| Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width 4000K 2500Im 83,33Im/W 80 80 80 80 80 80 80 80 80 8 | |
| Colour Temperature 4000K Lumen Output 2500lm Light Efficiency 83,33lm/W CRI 80 Beam Angle 38° Illumination Diagram Packing Info Box Length 25cm Box Width 10cm | |

Certification & Warranty

| Warranty | 2 Years |
|------------------|-------------|
| Average Lifetime | 30000 hours |
| Weee Directive | Yes |



