

www.1-light.eu

10 Track Spots>Mirror Square Track Spots

65906BT/B/W



30W COB LED track spot with, ideal for shops and showrooms.

Complete with 700mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads










Dimensions



Related items







40003A/B

Physical Specification

Item Group	10 Track Spots
Family	Mirror Square Track Spots
Order Code	65906BT/B/W
Colour	Black
Material	Die Cast
Shape	Rectangular
Length	119mm


Width	119mm
Height	148mm
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions
lostrical Characteristics	

Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	30W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	700mA
Voltage	40V
Power(Watts)	28W
Power(Watts) IP Rating	
	28W
IP Rating	28W IP20
IP Rating Light Source	28W IP20 LED built in
IP Rating Light Source LED Type	28W IP20 LED built in COB

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	28,9-29,4W
Power Factor	0,9
Constant Current	Yes
700mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Lifud
Illumination Data	
Illumination Data	
Illumination Data Colour Temperature	3000K
	3000K 2400lm
Colour Temperature	
Colour Temperature Lumen Output	2400lm
Colour Temperature Lumen Output Light Efficiency	2400lm 80lm/W
Colour Temperature Lumen Output Light Efficiency CRI	2400lm 80lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	2400lm 80lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	2400lm 80lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	2400lm 80lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	2400lm 80lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	2400lm 80lm/W 90 38°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Pcs/Carton	2400lm 80lm/W 90 38°



Certification & Warranty

Warranty 3 Years
Weee Directive Yes



