



## **Product Datasheet**

#### 15 Plafo>The LED Plafo Outdoor Round

### 67280AN/W/C



24W LED plafo light, IP65, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.











Downloads









#### Dimensions




#### **Physical Specification**

Item Group	15 Plafo
Family	The LED Plafo Outdoor Round
Order Code	67280AN/W/C
Colour	White
Material	Plastic
Diffuser Material	PC
Shape	Circular
Height	83mm
Diameter	300mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes

Adjustable	No
IK Rating	8
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	24W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	600mA
Voltage	38V
Power(Watts)	22,8W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
LED Number	121
F Mark	F
Gear	
Gear Type	Led Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	15,6-26W
Power Factor	0,9
Constant Current	Yes
600mA	26-43,5V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Eaglerise
llumination Data	
Colour Temperature	4000K
Colour Temperature  Lumen Output	4000K 1440lm
Lumen Output	1440lm
Lumen Output Light Efficiency	1440lm 60lm/W
Lumen Output Light Efficiency CRI	1440lm 60lm/W
Lumen Output Light Efficiency CRI Illumination Diagram	1440lm 60lm/W
Lumen Output Light Efficiency CRI	1440lm 60lm/W
Lumen Output Light Efficiency CRI Illumination Diagram	1440lm 60lm/W
Lumen Output  Light Efficiency  CRI  Illumination Diagram	1440lm 60lm/W 80
Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length	1440lm 60lm/W 80  30,5cm
Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width	1440lm 60lm/W 80 30,5cm
Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height	1440lm 60lm/W 80 30,5cm 30,5cm 8,5cm
Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height  Box Weight	1440lm 60lm/W 80 30,5cm 30,5cm 8,5cm 1,2Kg
Lumen Output  Light Efficiency  CRI  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height  Box Weight  Pcs/Carton	1440lm 60lm/W 80 30,5cm 30,5cm 8,5cm 1,2Kg



#### Certification & Warranty

Warranty	2 Years
Weee Directive	Yes

# switch to one light!

