



Product Datasheet

15 Plafo>Outdoor Slim LED Plafo Die cast

67362/AN/W



25W LED slim plafo, IP54, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.











Downloads









Dimensions



Physical Specification

Item Group	15 Plafo
Family	Outdoor Slim LED Plafo Die cast
Order Code	67362/AN/W
Colour	Anthracite
Material	Die Cast
Shape	Circular
Height	46mm
Diameter	238mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes
Adjustable	No

Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	25W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Type Input Current	Constant Current 350mA
Input Current	350mA
Input Current Voltage	350mA 67V
Input Current Voltage Power(Watts)	350mA 67V 23,45W
Input Current Voltage Power(Watts) IP Rating	350mA 67V 23,45W
Input Current Voltage Power(Watts) IP Rating Light Source	350mA 67V 23,45W IP54 LED built in
Input Current Voltage Power(Watts) IP Rating Light Source LED Type	350mA 67V 23,45W IP54 LED built in SMD 3014
Input Current Voltage Power(Watts) IP Rating Light Source LED Type LED Brand	350mA 67V 23,45W IP54 LED built in SMD 3014 Edison

Gear

Gear Type Led Driver

Input Voltage 220-240V


50 Hz Yes

60 Hz

Yes

Power(Watts)	17-25W
Power Factor	0,9
Constant Current	Yes
350mA	48-72V DC
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Eaglerise
Ilumination Data	
Colour Temperature	3000K
Lumen Output	1600lm
Light Efficiency	75lm/W
CRI	80
Beam Angle	120°
Illumination Diagram	
Packing Info	
Box Length	25,5cm
Box Width	25,5cm
Box Height	6,5cm
Box Weight	1,05kg
Pcs/Carton	8
Barcode	5291889039310
HS Code	9405409900

Energy Label



Certification & Warranty

Warranty	2 Years
Weee Directive	Yes



