

Product Datasheet

www.1-light.eu

23 LED Drivers>The 700mA Range

89030A



Constant current LED driver for 700mA LED spots / LED fittings, 15-30W.

Complies with standard EN61347-1 and any other specific standards.



Downloads



	000	ions
ווווכ	ens	IOLIS

L	160mm	-			
			58mm		20mm

Physical Specification

Item Group	23 LED Drivers
Family	The 700mA Range
Order Code	89030A
Material	Plastic
Shape	Rectangular
Length	160mm
Width	58mm

Height	18mm
Indoor	Yes

Electrical Characteristics



Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	15-30W
Power Factor	0,9
Constant Current	Yes
700mA	21,4-42,8V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	45°C
Operating Temp	85°C
Housing Material	Plastic
Output Terminal	Cable
Cable Length	15cm
Fast Connector	Yes
Fast Connector Type	One Light 700
Brand	One Light Ltd
Protection	Short Circuit / Overload / Overheat Protection

Packing Info	
Box Length	16,5cm

Box Width

7cm

Box Height	2cm
Box Weight	0,160kg
Pcs/Carton	100
Barcode	5291889035145
HS Code	8504408290



Warranty	5 Years
Weee Directive	Yes

switch to one light!

Certification & Warranty



