

# PRODUCT DESCRIPTION


- Installation of lighting and stretch films in suspension
- High lumen output
- Mounting to 12 mm | 0.47" drywall
- Non visible aluminum elements
- Line of light flush with the surface

### FINISH :

Non anodized (raw)

\*Custom colors available upon request

Fill empty fields



Product nr.

Fixture type

Company

Job name

Date

## **TECHNICAL SPECIFICATION**

### **Application**

- lighting recessed in surfaces made of stretch film and in drywall

### Mounting

- suspended or in drywall, using a dedicated mounting track, dedicated accessories and screws
- can be easily connected into runs
- the cover is cut to the length of the profile

### **Additional information**

- the profile has grooves for the attachment of the hooks from the stretch film


## AVAILABLE LENGTHS

Ref. nr.	surface finish	available lengths
C3632NA_1	Non anodized (raw)	1000 mm
C3632NA_2	Non anodized (raw)	2000 mm
C3632NA_3	Non anodized (raw)	3000 mm





# TECHNICAL DRAWING





# **RELATED PROFILES**



FOLHAK Profile Ref: B8338



FOLED-50-SUF Profile Ref: C3631



# **RELATED PRODUCTS**

COVERS

#### FROSTED COVERS



FOLED-50 frosted Cover Ref: 17171

### END CAPS

### REGULAR END CAPS



FOLED-50-W End cap Ref: 24294

#### STEEL



FOLED-50 End cap Ref: 42676

## ACCESSORIES

#### FASTENERS & MOUNTING ACCESSORIES



Spring hanger Ref: 79106



### COMPONENTS FOR CONNECTING PROFILES



ZM-NA-90 Connector Ref: 42723



ZM-NA-120

Connector

Ref: 42729

ZM-T45-G

Connector

Ref: 42324

ZM-X90-G

Connector

Ref: 42334

ZM-NA-PION-90 Connector Ref: 42726



ZM-X60-G Connector Ref: 42332



ZM-NA-PION-120 Connector Ref: 42321



Connector Ref: 42315

ZM-NA-PION-45



ZM-NA-180

Connector Ref: 42724

# SEALING COMPONENTS



6 x 1.2 Gland Ref: 00802



ZM-NA-135 Connector Ref: 42725



ZM-T60-G Connector Ref: 42326

ZM-Y120-G

Connector

Ref: 42336



ZM-NA-PION-135

Connector

Ref: 42727

Connector Ref: 42328



2 2 2 2