

**PRODUCT DESCRIPTION**

- For indoor/outdoor ground installation
- Designed for IP68 and IK10 protection ratings
- Corrosion resistance at high salinity
- Corresponds to the width of the HR-OPTI facade system

**FINISH :**

Non anodized (raw) 

\*Custom colors available upon request

Fill empty fields

Product nr.

Fixture type

Company

Job name

Date



**TECHNICAL SPECIFICATION**

**Application**

- warning and decorative lighting

**Mounting**

- in the ground, with mounting adhesive and a dedicated mounting track
- the cover is cut to the length of the profile

**Additional information**

- possibility of smooth transition from a recessed into a surface-mounted fixture
- use of clips facilitates the assembly of the lighting fixture

Application	driveway/ road/ floor lighting
Specific features	possibility of obtaining a line of light
Specific features	designated to be made waterproof (IP67)
Specific features	designated to be made waterproof (IP66)
Specific features	designated to be made waterproof (IP68)
Material	Aluminium
Finish	Non anodized (raw)
place of installation	outdoor installation

Mounting method	recess mount
Number of LED strips	1
the possibility of bending	no
Length	3.00&nbsp;spm


**RELATED PROFILES**



HR-MAX-T Profile  
Ref: C1827



HR-MAX-TW  
Profile  
Ref: C1828



HR-MAX Profile  
Ref: C1829

## RELATED PRODUCTS

### COVERS

#### SEMI-TRANSPARENT COVERS



HR-21 frosted  
Cover  
Ref: 17152

### END CAPS

#### STEEL



HR-MAX-STN End  
cap  
Ref: 24388



HR-MAX-TK-STN  
End cap  
Ref: 24391



HR-MAX-T-STN  
End cap  
Ref: 24389

### ACCESSORIES

#### SEALING COMPONENTS



Hermetic splitter  
Ref: 42703



Hermetic coupler  
Ref: 42702




M16 x 1.5 Gland  
Ref: 42271



M16 x 1,5 - L90  
Angular gland  
Ref: 42289

#### ADDITIONAL ITEMS



TECH-35  
protective insert  
Ref: 17127



HR-MAX clip  
Ref: 24416



HR-MAX Pad  
Ref: 70547

MARKETING MATERIALS



Foam 70569  
Ref: 70569



Display  
P230-90223M  
Ref: 90223M