

## PRODUCT DESCRIPTION

- For installation on facades
- Designed for IP68 and IK10 protection ratings
- Corrosion resistance at high salinity
- Corresponds to the width of the HR-MAX facade system
- Adjustable lighting angle

Fill empty fields

Product nr.

Fixture type

Company

Job name

Date



## TECHNICAL SPECIFICATION

### Application

- decorative lighting

### Mounting


- to the surface, using dedicated accessories
- the cover is cut to the length of the profile

### Additional information

- possibility to fasten the lighting fixture with the back or side to the mounting surface
- possibility of smooth transition from a surface-mounted into a recessed fixture

Application	facade lighting
Specific features	possibility of obtaining a line of light
Specific features	designated to be made waterproof (IP66)
Specific features	designated to be made waterproof (IP68)
Specific features	designated to be made waterproof (IP67)
Material	Aluminium
place of installation	outdoor installation
Mounting method	surface mount
Number of LED strips	1
the possibility of bending	no
Length	3.00&nbsp;spm

## RELATED PROFILES



HR-OPTI Profile  
Ref: C1844

## RELATED PRODUCTS

### COVERS

#### SEMI-TRANSPARENT COVERS



HR-21 frosted  
Cover  
Ref: 17152

### END CAPS

#### STEEL



HR-OPTI-STN End  
cap  
Ref: 24387

### ACCESSORIES

#### FASTENERS & MOUNTING ACCESSORIES



HR-OPTI Mounting  
bracket  
Ref: 42121



HR-OPTI-A  
Mounting bracket  
Ref: \_

#### SEALING COMPONENTS



Hermetic splitter  
Ref: 42703



Hermetic coupler  
Ref: 42702



M16 x 1.5 Gland  
Ref: 42271



M16 x 1,5 - L90  
Angular gland  
Ref: 42289

MARKETING MATERIALS



Foam 70570  
Ref: 70570



Display  
P230-90223M  
Ref: 90223M