

PRODUCT DESCRIPTION

- Flexible cover with increased UV resistance
- Snapped-in

Fill empty fields

Product nr.

Fixture type

Company

Job name


Date




TECHNICAL SPECIFICATION

Material	PC
Available length	1000 mm, 2000 mm, 3000 mm
UV resistance	increased


TECHNICAL DRAWING




RELATED PROFILES




OPK-4 Profile
Ref: C0370




MICRO-H Profile
Ref: C0599




PDS-H Profile
Ref: B9204




45-16 Profile
Ref: B8504




OLEK Profile
Ref: B8505




MICRO-ALU Profile
Ref: B1888



MICRO-K Profile
Ref: B3775




PDS-4-ALU Profile
Ref: B1718




PDS-4-K Profile
Ref: B3776




PDS-ZM Profile
Ref: B7696




POR Profile
Ref: B6144




PDS-O Profile
Ref: B3777




45-ALU Profile
Ref: B4023




GLAD-45 Profile
Ref: B7009




KUBIK-45 Profile
Ref: B7697




KOZMA Profile
Ref: 18040




DES Profile
Ref: 18030




POLI Profile
Ref: B7176



NISA-PLA Profile
Ref: 18028




NISA-KON Profile
Ref: 18027




NISA-KRA Profile
Ref: 18026




NISA-NI Profile
Ref: 18029



STEP Profile
Ref: 18042




PULA Profile
Ref: 18035




OBIT Profile
Ref: W4826




LIT-L Profile
Ref: 18033




PDS-4-PLUS
Profile
Ref: C1263




PDS-ZMG Profile
Ref: C1418




MICRO-HG Profile
Ref: C1419




MOD-50 Profile
Ref: 18047




PDS-NK Profile
Ref: C1588




MICRO-NK Profile
Ref: C1587




MOD-100 Profile
Ref: 18049




PDS-T Profile
Ref: C2057



PDS-ZM-PLUS
Profile
Ref: C2056



PDS-UST Profile
Ref: C2725



MICRO-PLUS
Profile
Ref: C2966