

PRODUCT DESCRIPTION

- Flexible cover with increased UV resistance
- Snapped-in

Fill empty fields

Product nr.

Fixture type


Company

Job name


Date

**TECHNICAL SPECIFICATION**


Material	PC
Available length	1000 mm, 2000 mm, 3000 mm
UV resistance	increased

TECHNICAL DRAWING

RELATED PROFILES



OPK-4 Profile
Ref: C0370




MICRO-H Profile
Ref: C0599




PDS-H Profile
Ref: B9204




45-16 Profile
Ref: B8504



OLEK Profile
Ref: B8505




MICRO-ALU Profile
Ref: B1888




MICRO-K Profile
Ref: B3775



PDS-4-ALU Profile
Ref: B1718




PDS-4-K Profile
Ref: B3776




PDS-ZM Profile
Ref: B7696




POR Profile
Ref: B6144




PDS-O Profile
Ref: B3777




45-ALU Profile
Ref: B4023




GLAD-45 Profile
Ref: B7009



KUBIK-45 Profile
Ref: B7697



KOZMA Profile
Ref: 18040




DES Profile
Ref: 18030




POLI Profile
Ref: B7176



NISA-PLA Profile
Ref: 18028



NISA-KON Profile
Ref: 18027




NISA-KRA Profile
Ref: 18026




NISA-NI Profile
Ref: 18029



STEP Profile
Ref: 18042




PULA Profile
Ref: 18035




OBIT Profile
Ref: W4826




LIT-L Profile
Ref: 18033




PDS-4-PLUS
Profile
Ref: C1263




PDS-ZMG Profile
Ref: C1418




MICRO-HG Profile
Ref: C1419




MOD-50 Profile
Ref: 18047




PDS-NK Profile
Ref: C1588




MICRO-NK Profile
Ref: C1587




MOD-100 Profile
Ref: 18049




PDS-T Profile
Ref: C2057



PDS-ZM-PLUS
Profile
Ref: C2056



PDS-UST Profile
Ref: C2725



MICRO-PLUS
Profile
Ref: C2966

RELATED PRODUCTS

END CAPS



ONISA grey End
cap
Ref: 24100