KLUŚ ® | **Inspiring Solutions**

PRODUCT DESCRIPTION

■ Basic cover dedicated to all standard Kluś extrusions

Fill empty fields

Product nr.

Fixture type

Company

Job name

Date

TECHNICAL SPECIFICATION

| Material	PC
Available length	1000 mm, 2000 mm, 3000 mm
UV resistance	no

TECHNICAL DRAWING

[0.157in] 4mm

[0.512in] 13mm

RELATED PROFILES


OPK-4 Profile
Ref: C0370

MICRO-H Profile
Ref: C0599


PDS-H Profile
Ref: B9204



45-16 Profile
Ref: B8504

OLEK Profile
Ref: B8505

MICRO-ALU Profile
Ref: B1888

MICRO-K Profile
Ref: B3775

PDS-4-ALU Profile
Ref: B1718


PDS-4-K Profile
Ref: B3776


PDS-ZM Profile
Ref: B7696

POR Profile
Ref: B6144

PDS-O Profile
Ref: B3777

45-ALU Profile
Ref: B4023

GLAD-45 Profile
Ref: B7009

KUBIK-45 Profile
Ref: B7697

KOZMA Profile
Ref: 18040

DES Profile
Ref: 18030

POLI Profile
Ref: B7176

NISA-PLA Profile
Ref: 18028

NISA-KON Profile
Ref: 18027

NISA-KRA Profile
Ref: 18026


NISA-NI Profile
Ref: 18029


STEP Profile
Ref: 18042

PULA Profile
Ref: 18035

OBIT Profile
Ref: W4826

LIT-L Profile
Ref: 18033

PDS-MDF Profile
Ref: 0971

STOS-MDF Profile
Ref: 0974

45-MDF Profile
Ref: 0973

PAC-MDF Profile
Ref: 0972

PDS-4-PLUS
Profile
Ref: C1263

PDS-ZMG Profile
Ref: C1418

MICRO-HG Profile
Ref: C1419

MOD-50 Profile
Ref: 18047

PDS-NK Profile
Ref: C1588

MICRO-NK Profile
Ref: C1587

MOD-100 Profile
Ref: 18049

PDS-T Profile
Ref: C2057

PDS-ZM-PLUS
Profile
Ref: C2056

PDS-UST Profile
Ref: C2725

MICRO-PLUS
Profile
Ref: C2966