

PRODUCT DESCRIPTION

- Mounting to 16 mm / 0.63" drywall boards
- No collision with the ceiling structure
- Line of light flush with the surface
- High lumen output
- Non visible aluminum elements

FINISH :

Non anodized (raw)

*Custom colors available upon request

Fill empty fields

Product nr.

Fixture type

Company

Job name

Date

TECHNICAL SPECIFICATION

Application

- main, decorative and functional lighting.

Mounting

- in drywall, with mounting adhesive,
- can be easily connected into runs,
- the cover is cut to the length of the profile.

Additional information

- in order to protect the lighting fixture during installation, a TECH-50 protective insert should be used.

AVAILABLE LENGTHS


| Ref. nr. | surface finish | available lengths |
|-----------|--------------------|-------------------|
| C0958NA_1 | Non anodized (raw) | 1000 mm |
| C0958NA_2 | Non anodized (raw) | 2000 mm |
| C0958NA_3 | Non anodized (raw) | 3000 mm |







TECHNICAL DRAWING





RELATED PRODUCTS

COVERS

BLACK COVERS



LIGER-50 black Cover Ref: 17089

FROSTED COVERS



Cover Ref: 17086

END CAPS

REGULAR END CAPS



KOZUS-50 grey End cap Ref: 24282

ACCESSORIES

COMPONENTS FOR CONNECTING PROFILES





ZM-NA-90 Connector Ref: 42723



Connector

Ref: 42726



ZM-NA-120

Connector

ZM-NA-45

Connector

Ref: 42339



ZM-NA-135 Connector Ref: 42725

Ref: 42321



ZM-NA-PION-120 Connector



ZM-NA-PION-135

Connector

ZM-NA-PION-60 Connector Ref: 42317





ZM-NA-PION-45 Connector Ref: 42315

ZM-NA-180 Connector Ref: 42724

SEALING COMPONENTS



6.4 x 3.0 Gland Ref: 42264

ADDITIONAL ITEMS



TECH-50 protective insert Ref: 17125

MARKETING MATERIALS









Foam 70265 Ref: 70265

Display P230-90155M Ref: 90155M