

PRODUCT DESCRIPTION

The cover has a matt black surface that turns white when the light is turned on, the line of light at 160LED/m. The cover material is PC (polycarbonate) with increased resistance to UV radiation. The best visual effect is obtained with profiles that are black inside. The cover creates a line of light in profiles minimal deep 11 mm at 160LED/1m.

- They blend in with dark lighting fixtures and dark surfaces of ceilings or walls
- A surprising light effect when the light is switched on

Fill empty fields

Product nr.

Fixture type

Company

Job name

Date



TECHNICAL SPECIFICATION

Application


- decorative lighting

Mounting

- snap-in in dedicated profiles

Material	PC
Available length	1000 mm, 2000 mm, 3000 mm
UV resistance	increased

TECHNICAL DRAWING





RELATED PROFILES



OPK-4 Profile Ref: C0370



MICRO-H Profile Ref: C0599



PDS-H Profile Ref: B9204



45-16 Profile Ref: B8504



OLEK Profile Ref: B8505



Ref: B1888



MICRO-ALU Profile MICRO-K Profile Ref: B3775



PDS-4-ALU Profile Ref: B1718



PDS-4-K Profile Ref: B3776



PDS-ZM Profile Ref: B7696



POR Profile Ref: B6144



PDS-O Profile Ref: B3777



45-ALU Profile Ref: B4023



GLAD-45 Profile Ref: B7009



KUBIK-45 Profile Ref: B7697



KOZMA Profile Ref: 18040



DES Profile Ref: 18030



POLI Profile Ref: B7176



NISA-PLA Profile Ref: 18028



NISA-KON Profile Ref: 18027



NISA-KRA Profile Ref: 18026



NISA-NI Profile Ref: 18029



STEP Profile Ref: 18042



PDS-4-PLUS Profile Ref: C1263





PDS-ZMG Profile Ref: C1418



MICRO-HG Profile Ref: C1419



MOD-50 Profile Ref: 18047



PDS-NK Profile Ref: C1588



MICRO-NK Profile Ref: C1587



PDS-T Profile Ref: C2057



PDS-ZM-PLUS Profile Ref: C2056



PDS-UST Profile Ref: C2725



MICRO-PLUS Profile Ref: C2966



RELATED PRODUCTS

MARKETING MATERIALS





Display P230-90154M Ref: 90154M

Foam 70271 Ref: 70271