



PRODUCT DESCRIPTION

- Fits all basic KLUŚ extrusions
- Cover dedicated to creating a line of light
- We recommend it to be used with bent extrusions
- Very good light diffusion
- The product is available in a 10 m roll

Fill empty fields

Product nr.

Fixture type

Company


Job name

Date

TECHNICAL SPECIFICATION

Material	PC
Available length	1000 mm, 2000 mm, 3000 mm, 10000 mm
UV resistance	increased

TECHNICAL DRAWING







RELATED PROFILES



OPK-4 Profile Ref: C0370





MICRO-H Profile Ref: C0599

Ref: B1888

PDS-ZM Profile

GLAD-45 Profile

Ref: B7009

POLI Profile

Ref: B7176

Ref: B7696



OLEK Profile Ref: B8505



PDS-4-K Profile Ref: B3776



45-ALU Profile Ref: B4023




DES Profile Ref: 18030



NISA-KRA Profile Ref: 18026



NISA-NI Profile Ref: 18029




PDS-H Profile Ref: B9204



MICRO-ALU Profile MICRO-K Profile Ref: B3775



45-16 Profile Ref: B8504



PDS-4-ALU Profile Ref: B1718



PDS-O Profile Ref: B3777





NISA-KON Profile Ref: 18027



PULA Profile Ref: 18035









STEP Profile Ref: 18042

Ref: B7697













OBIT Profile Ref: W4826



LIT-L Profile Ref: 18033



MICRO-HG Profile Ref: C1419





MOD-100 Profile Ref: 18049



MICRO-PLUS Profile Ref: C2966





PDS-T Profile Ref: C2057



PDS-4-PLUS Profile Ref: C1263




PDS-NK Profile Ref: C1588

PDS-ZM-PLUS

Ref: C2056

Profile



PDS-UST Profile Ref: C2725

MICRO-NK Profile

51

Ref: C1587



PDS-ZMG Profile Ref: C1418