

PRODUCT DESCRIPTION

Profile designed to eliminate the need to cut the cover due to end caps.

Wide range of accessories

- Low height
- Smooth profile surfaces
- Small bending radius

FINISH :

Silver anodized

Black anodized

*Custom colors available upon request



	Fill empty fields
Product nr.	
Fixture type	
Company	
Job name	
Date	

TECHNICAL SPECIFICATION

Application

- furniture and decorative lighting

Mounting

- to the surface, suspended or recessed, using dedicated accessories, properly selected screws, double-sided adhesive tape or mounting adhesive,

- the cover is cut to the length of the profile,

- easy assembly and disassembly by snapping in and out.

Additional information

- possibility of building a linear fixture with IP67 protection, which means the fixture is dustproof and waterproof,
- IP67 is possible with the following covers: LIGER, KA, HS, KA-PRO and KA-COM,
- can be equipped with transparent and frosted covers (diffusers), aluminum-colored plastic end caps,

- space for LED strip: 11.2 mm.

Profile bending

bent lighting fixture	Minimum radius for a bent lighting fixture directing light outwards
150 mm	150 mm



- minimum radius - bending radius which when exceeded causes destruction (deformation, bending or lack of compatibility with other accessories, e.g. covers, end caps, etc.) of the profile,


- internal radius refers to the profile bent so that the cover is facing the inside of the arch,
- external radius refers to the profile bent so that the cover is facing the outside of the arch,
- irregular curves are possible after consultation and individual quotation,

- when bending anodized profiles, one should be aware of cracking of the anode coating (which may be more or less visible depending on the radius).

AVAILABLE LENGTHS

Ref. nr.	surface finish	available lengths
C2966ANODA_1	Silver anodized	1000 mm
C2966ANODA_2	Silver anodized	2000 mm
C2966ANODA_3	Silver anodized	3000 mm
C2966K7_1	Black anodized	1000 mm
C2966K7_2	Black anodized	2000 mm
C2966K7_3	Black anodized	3000 mm

TECHNICAL DRAWING





RELATED PRODUCTS

COVERS

BLACK COVERS



LIGER black Cover Ref: 17040

CLEAR COVERS




KA clear Cover

Ref: 17036



Ref: 1370



KA-COM clear Cover Ref: 17122



Cover Ref: 17065

FROSTED COVERS







M-K frosted Cover KA-PRO frosted Cover Ref: 17064



HS frosted Cover Ref: 1369



Ref: 17038

KA-COM frosted Cover Ref: 17121

LIGER frosted Cover Ref: 17037

END CAPS

REGULAR END CAPS





MICRO-PLUS grey End cap Ref: 24392

MICRO-PLUS black End cap Ref: 24419

REGULAR END CAPS WITH HOLE





black End cap Ref: 24420

MICRO-PLUS-OTW MICRO-PLUS-OTW grey End cap Ref: 24393

ACCESSORIES

FASTENERS & MOUNTING ACCESSORIES



PDS-STN-90G Mounting bracket Ref: 24370



PDS-STN-ALFA Mounting bracket Ref: 24426



PLANISA Mounting bracket Ref: 24121



PDS-STN

PDS Mounting bracket Ref: 24189



REG-PD-UV Mounting bracket Ref: 24190



PDS-STN-90D Mounting bracket Ref: 24367





PDS Spring Ref: 00800







PDS Mounting bracket Ref: 24223





ST Head Ref: 42216



ZO Head Ref: 42217



PUSZ-LIN-MR Fastener white Ref: 42278L9010



PUSZ-PRET-MR Fastener Ref: 42252



DP-ZZ Fastener Ref: 00651



Fastener

Ref: 00647

DP-MOC-ZZ



Fastener



BZP-ZZ Head Ref: 42215



PUSZ-PRET-MR Fastener silver Ref: 42281

PUSZ-PRET-MR

Fastener white

PUSZ-LIN-MR

Fastener

Ref: 42258

Ref: 42281L9010



Fastener silver

Ref: 42278

BZP-ZO Head

Ref: 42214

PUSZ-LIN-MR Fastener black Ref: 42278L9005



FI-8-LIN-MR Fastener black Ref: 42287L9005



DP-ZO Fastener Ref: 00649



DP-MOC Fastener Ref: 00645



DP-MOC-ZO Ref: 00646

COMPONENTS FOR CONNECTING PROFILES



ZZ Head Ref: 42218



PUSZ-PRET-MR Fastener black Ref: 42281L9005



FI-8-LIN-MR Fastener white Ref: 42287L9010



FI-8-LIN-MR Fastener silver







PD-MICRO Connector Ref: 42150

MOUNTING SETS



Ref: 42602





Ref: 42609

black

Ref: 42647L9005



M5 Fastener set Ref: 42302



W10 Fastener set M11 Fastener set Ref: 42608



M14 Fastener set Ref: 42612



RG-1 Fastener set silver satin Ref: 42647GSS





M3 Fastener set Ref: 42303



W7 Fastener set Ref: 42605



M12 Fastener set Ref: 42610



RG-1 Fastener set RG-1 Fastener set silver Ref: 42647NI

M13 Fastener set Ref: 42611

li i


W9 Fastener set

Ref: 42607



RG-1 Fastener set white Ref: 42647L9010













6 x 1.2 Gland Ref: 00802

LED TAPES

WHITE



LONG RUN

	nin∦e¢rinin	

LED strip K-LR-1000-24V Ref: K-LR-1000-24V

CRI 95+



20 8 1 8 4 8 1 8	(n um fu nic)(n um da)nic)(n narf	[ของสุขาวัน]ิยาย (ของัน) และสู่	ļiņa ģiņa ģiņ
LED strip K-	LED strip K-	LED strip K-	LED strip K-
CR-1210-24V	CR-1220-24V	CR-1275-24V	CR-1820-HD-24V
Ref: K-	Ref: K-	Ref: K-	Ref: K-CR-1820-
CR-1210-24V	CR-1220-24V	CR-1275-24V	HD-24V



LED strip K-CR-1910-HD-24V Ref: K-CR-1910-HD-24V

RGB / RGB-W

	. (• . *• . • . • . • . • . • . • . • . • .	∄ਮ ਸਮਨਨਨ ≣ੂਮ ਸਨਨਨਨ ⊒ਮ ਸਨਨ	[]={#66#]={#66#]=4#
LED strip K-1275- RGB-12V Ref: K-1275- RGB-12V	LED strip K-1275- RGB-24V Ref: K-1275- RGB-24V	LED strip K-1530- RGB+W-24V Ref: K-1530- RGB+W-24V	LED strip K-1920-120-RGB-24V 19.2W/m Ref: K-1920-120- RGB-24V

TUNABLE WHITE / DIM TO WARM

{n _ n = n = n = n = n = n = . n	្តំមក ស្ថាន នាក់ ស្ថាន ដែន និ	(
LED strip	LED strip	LED strip
K-27/65-1920-24V	K-22/50-1728-24V	K-30/18-1770-24V
Ref:	Ref:	Ref:
K-27/65-1920-24V	K-22/50-1728-24V	K-30/18-1770-24V

MARKETING MATERIALS



Presentation set 1 Ref: 90051