

PRODUCT DESCRIPTION

- Mounting track
- Mounting to 12 mm / 0.47" drywall boards
- Easy servicing of the lighting fixture
- Stable moutning to a suspended ceiling
- Non visible aluminum elements

FINISH:

Non anodized (raw)



*Custom colors available upon request



Fill empty fields

Product nr.

Fixture type

Company

Job name

Date

TECHNICAL SPECIFICATION

Application

- makes installation and service of lighting fixtures easy.

Mounting

- in drywall, with screws,
- can be easily connected into runs.

Additional information


- while finishing a surface with the TEKNIK-ZM profile inserted, its interior must be protected against contamination,
- lighting fixtures compatible with the TEKNIK-ZM profile are connected using TEKNIK latches,
- TEKNIK latches needs to be purchased separately.

AVAILABLE LENGTHS

Ref. nr.	surface finish	available lengths
C0399NA_1	Non anodized (raw)	1000 mm
C0399NA_2	Non anodized (raw)	2000 mm
C0399NA_3	Non anodized (raw)	3000 mm



TECHNICAL DRAWING





RELATED PROFILES







GIZA Profile Ref: B5556



LIPOD Profile Ref: B5554



LOKOM Profile Ref: B5553



RELATED PRODUCTS

END CAPS

REGULAR END CAPS



TEKNIK-ZM grey End cap Ref: 24264

ACCESSORIES

FASTENERS & MOUNTING ACCESSORIES



TEKNIK Latch Ref: 24003

COMPONENTS FOR CONNECTING PROFILES



ZM-NA-90 Connector Ref: 42723



ZM-NA-135 Connector Ref: 42725



ZM-NA-PION-135 Connector Ref: 42727



ZM-NA-PION-90 Connector Ref: 42726



ZM-NA-45 Connector Ref: 42339



ZM-NA-PION-120 Connector Ref: 42321



ZM-NA-PION-60 Connector Ref: 42317



ZM-NA-PION-45 Connector Ref: 42315





ZM-NA-180 Connector Ref: 42724

SEALING COMPONENTS



6 x 1.2 Gland Ref: 00802

ADDITIONAL ITEMS



TECH-28 protective insert Ref: 17168

MARKETING MATERIALS



Display P230-90072M Ref: 90072M



Display P230-90102M Ref: 90102M



Presentation set 2 Foam 70266 Ref: 90052



Ref: 70266