

PRODUCT DESCRIPTION

- Mounting track
- Mounting to 16 mm / 0.63" drywall boards
- Easy servicing of the lighting fixture
- Stable moutning to a suspended ceiling
- Non visible aluminum elements

FINISH :

Non anodized (raw)

*Custom colors available upon request

Fill empty fields

Product nr.

Fixture type

Company

Job name

Date

TECHNICAL SPECIFICATION

Application

- makes installation and service of lighting fixtures easy

Mounting

- in drywall, with screws,

- can be easily connected into runs.


AVAILABLE LENGTHS

Ref. nr.	surface finish	available lengths
C1293NA_1	Non anodized (raw)	1000 mm
C1293NA_2	Non anodized (raw)	2000 mm
C1293NA_3	Non anodized (raw)	3000 mm

TECHNICAL DRAWING










RELATED PROFILES











LOKOM Profile Ref: B5553

GIZA-LL profile Ref: C0758

GIZA Profile Ref: B5556

LIPOD Profile Ref: B5554



RELATED PRODUCTS

END CAPS

REGULAR END CAPS



TEKUS-ZM grey End cap Ref: 24313

ACCESSORIES

FASTENERS & MOUNTING ACCESSORIES



TEKNIK Latch Ref: 24003

COMPONENTS FOR CONNECTING PROFILES







ZM-NA-135 Connector Ref: 42725



ZM-NA-PION-135 Connector Ref: 42727



Ref: 42726



ZM-NA-180 Connector Ref: 42724

MARKETING MATERIALS





Presentation set 2 Ref: 90052