

PRODUCT DESCRIPTION

- Mounting track
- Mounting to 12 mm / 0.47" drywall boards
- Easy servicing of the SEKOMA profile
- Stable moutning to a suspended ceiling
- Non visible aluminum elements

FINISH :

Non anodized (raw)

*Custom colors available upon request

Fill empty fields

Product nr.

Fixture type

Company

Job name

Date

TECHNICAL SPECIFICATION

Application

- makes mounting and service of the SEKOMA profile easy.

Mounting

- in drywall, with screws.

Additional information

- the profile is sold together with blok springs. The Blok springs are mounted in pairs, depending on the profile length: 2 pcs. up to a length of 15cm, 4 pcs. from 15cm to 1m, 6 pcs. up to a length of 2m, 8 pcs. up to a length of 3m


AVAILABLE LENGTHS

Ref. nr.	surface finish	available lengths
18021V1NA_1	Non anodized (raw)	1000 mm
18021V1NA_2	Non anodized (raw)	2000 mm
18021V1NA_3	Non anodized (raw)	3000 mm






TECHNICAL DRAWING





RELATED PROFILES



SEKOMA Profile Ref: B6595



RELATED PRODUCTS

ACCESSORIES

FASTENERS & MOUNTING ACCESSORIES



BLOK Spring Ref: 42731V1

MARKETING MATERIALS



Presentation set 4 Ref: 90054