

PRODUCT DESCRIPTION

The information contained in the description applies to the PK-4 system (a set of TPK-4 and OPK-4 profiles, and the PK-4 mounting bracket)

- Mounting track
- Easy servicing of the OPK-4 profile
- Mounting to drywall boards
- No collision with the ceiling structure
- Non visible aluminum elements

FINISH:

Non anodized (raw)



*Custom colors available upon request



Fill empty fields

Product nr.

Fixture type

Company

Job name

Date

TECHNICAL SPECIFICATION

Application

- makes mounting and service of the OPK-4 profile easy.

Mounting

- in drywall, with mounting adhesive,
- can be easily connected into runs.

Additional information

- it replaces the old TE-4 system
- it is fitted with a mounting bracket and the TPK-4 protective insert, which protects essential elements against soiling during assembly


AVAILABLE LENGTHS

Ref. nr.	surface finish	available lengths
18044NA_1	Non anodized (raw)	1000 mm
18044NA_2	Non anodized (raw)	2000 mm




Ref. nr.	surface finish	available lengths
18044NA_3	Non anodized (raw)	3000 mm

TECHNICAL DRAWING





RELATED PROFILES



OPK-4 Profile Ref: C0370



RELATED PRODUCTS

END CAPS

REGULAR END CAPS



TPK-4 grey End cap Ref: 24239

ACCESSORIES

COMPONENTS FOR CONNECTING PROFILES



ZM-NA-90 Connector Ref: 42723



ZM-NA-120 Connector Ref: 42729



ZM-NA-135 Connector Ref: 42725



ZM-NA-PION-135 Connector Ref: 42727



ZM-NA-PION-90 Connector Ref: 42726



ZM-NA-45 Connector Ref: 42339



ZM-NA-PION-120 Connector Ref: 42321



ZM-NA-PION-60 Connector Ref: 42317



ZM-NA-PION-45 Connector Ref: 42315



ZM-NA-180 Connector Ref: 42724

SEALING COMPONENTS



6 x 1.2 Gland Ref: 00802



ADDITIONAL ITEMS



PK-4 Disassembly plates Ref: 70261

MARKETING MATERIALS







Ref: 70267



PK-4 two-display installation Ref: 90148