

Technical information

Physical	
Material	Shade: die-cast aluminium Canopy: polyamide
Optics	Lens: PMMA Reflector: polycarbonate
IP rating	20
Protection class	II

LED	
Light source	PAR16 – GU10
Lifetime expectancy	L70 / 25,000 h
CRI Colour rendering index	90
Stand. deviation of colour	3-step MacAdam
Replaceable light source by end-user	

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The applicable General Terms & Conditions apply.

Article-specific information

Mounting
LED Colour temperature (CCT) / Luminous flux
Voltage / System power
Light control
Net weight
Packaging dimensions
Gross weight

2700 K Colour temperature (CCT)		
Traffic white (RAL 9016)		
Jet black (RAL 9005)		
Silver grey (similar to RAL 9006)		
Pure orange (RAL 2004)		
Zink yellow (RAL 1018)		
Beige (RAL 1001)		
Traffic red (RAL 3020)		
Sapphire blue (RAL 5003)		
Grass green (RAL 6010)		
Sepia brown (RAL 8014)		

3000 K Colour temperature (CCT)		
Traffic white (RAL 9016)		
Jet black (RAL 9005)		
Silver grey (similar to RAL 9006)		
Pure orange (RAL 2004)		
Zink yellow (RAL 1018)		
Beige (RAL 1001)		
Traffic red (RAL 3020)		
Sapphire blue (RAL 5003)		
Grass green (RAL 6010)		
Sepia brown (RAL 8014)		

Accessories	
1-phase track adapter white	
1-phase track adapter black	
3-phase track adapter white	
3-phase track adapter black	

w131 Bell



Ceiling suspended
2700 K / 437 lm 3000 K / 457 lm
110–240 V / 6.5 W
Phase-cut dim
0.6 kg
Box 1: L16 × W16.5 × H16 cm (0.005 m³) Box 2: L5.5 × W5.5 × H6.7 cm (0.0002 m³)
Box 1: 1 kg Box 2: 0.1 kg

Art. No. / EAN code	
131S1901627 / 7330492002323	
131S1900527 / 7330492002255	
131S1111127 / 7330492002231	
131S1200427 / 7330492002248	
131S1101827 / 7330492002262	
131S1100127 / 7330492002279	
131S1302027 / 7330492002286	
131S1500327 / 7330492002293	
131S1601027 / 7330492002309	
131S1801427 / 7330492002316	

Art. No. / EAN code	
131S1901630 / 7330492002422	
131S1900530 / 7330492002354	
131S1111130 / 7330492002330	
131S1200430 / 7330492002347	
131S1101830 / 7330492002361	
131S1100130 / 7330492002378	
131S1302030 / 7330492002385	
131S1500330 / 7330492002392	
131S1601030 / 7330492002408	
131S1801430 / 7330492002415	

Art. No. / EAN code	
ACC00102 / 7330492001920	
ACC00105 / 7330492001937	
ACC00202 / 7330492001944	
ACC00205 / 7330492001951	